


AT-O-0.5-3-N




Key Specifications

Operating frequency band	500 MHz - 3 GHz
Connector	N type female
VSWR	< 2:1
Gain	2-6.5 dBi
3dB Beamwidth	30-90 degrees
Polarization	linear/vertical
Size	height 19.5cm, length 21.5cm, width 6cm
Power	100 W c.w.


This wideband blade antenna covers 500 MHz–3 GHz frequency range and provides broadband performance for communication, telemetry, monitoring, and platform-mounted RF applications. Its rugged low-profile structure, N-type connector, and wide operating bandwidth make it suitable for UAV, vehicle, fixed-site, and mobile installations where compact form, durable construction, and stable signal performance are required.

Please contact AntennaTec for a full interface control drawing.


VSWR




S11



Gain



Beamwidth




AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.




Radiation Patterns: Red = Azimuth; Green = Elevation


0.5GHz




1GHz




1.5GHz




2GHz



2.5GHz



3GHz



AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.

