

1.1-1.7 GHz circularly polarized helical antenna fitted with an N type connector and radome

AT-HL-1.1-1.7-N



Key Specifications


Operating frequency band	1.1 - 1.7 GHz
Connector	N type female
VSWR	< 2:1
Gain	> 10 dBi
3dB Beamwidth	30-60 degrees
Polarization	circular polarization
Size	length 50cm, dia 24cm
Axial Ratio	< 1.5dbi

This circularly polarized helical antenna designed for reliable long-range wireless communication across 1.1–1.7 GHz frequency range. Featuring directional gain greater than 10 dBi, a durable radome enclosure, it delivers strong signal performance, reduced sensitivity to antenna orientation, and excellent polarization characteristics. This antenna is ideal for drone jamming, tracking systems, remote sensing, and other RF applications requiring stable and efficient wireless links.

Please contact AntennaTec for a full interface control drawing.


VSWR

Voltage Standing Wave Ratio (VSWR)




S11

S-Parameters [Magnitude]




Gain

Max Gain over Frequency



Axial Ratio

Axial Ratio




AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.




Radiation Patterns: Red = Phi 0; Green = Phi 90


1.1GHz




1.3GHz




1.42GHz




1.5GHz



1.54GHz



1.62GHz



AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.

