

AT-HL-4.2-5.5-N




Key Specifications

Operating frequency band	4.2 - 5.5 GHz
Connector	N type female
VSWR	< 2:1
Gain	> 10 dBi
3dB Beamwidth	25-40 degrees
Polarization	circular polarization
Size	length 25cm, width 15cm
Axial Ratio	< 2dbi


This high-gain helical antenna covers 4.2–5.5 GHz frequency range and provides circularly polarised directional performance for compact high-frequency wireless links. Its more than 10 dBi gain, controlled beamwidth, and radome-protected structure make it suitable for C-band telemetry, drone jamming, point-to-point communication, tracking systems, and field-deployed RF applications requiring stable polarisation and focused radiation.

Please contact AntennaTec for a full interface control drawing.


VSWR




S11



Gain



Axial Ratio




AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.




Radiation Patterns: Red = Phi 0; Green= Phi 90


4.2GHz




4.4GHz




4.6GHz




4.9GHz



5.2GHz



5.5GHz



AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.

