


AT-HL-4.4-6.4-N




Key Specifications

Operating frequency band	4.4 - 6.4 GHz
Connector	N type female
VSWR	< 2:1
Gain	> 12 dBi
3dB Beamwidth	25-30 degrees
Polarization	circular polarization
Size	length 22cm, width 15cm
Axial Ratio	< 2dbi


This circularly polarised helical antenna operates across 4.4–6.4 GHz frequency band and delivers more than 12 dBi gain for focused high-frequency RF communication. Its compact helical design, stable axial-ratio performance, and narrow directional beam make it suitable for drone jamming, C-band wireless systems, telemetry, tracking, video transmission, and demanding operating scenarios where long-range link stability is required.

Please contact AntennaTec for a full interface control drawing.


VSWR




S11



Gain



Axial Ratio




AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.




Radiation Patterns: Red = Phi 0; Green = Phi 90


4.4GHz




4.8GHz




5.2GHz




5.6GHz



6GHz



6.4GHz



AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.

