

AT-HL-5.72-5.88-N



Please contact AntennaTec for a full interface control drawing.


Key Specifications

Operating frequency band	5.72-5.88 GHz
Connector	N type female
VSWR	< 1.5:1
Gain	> 16 dBi
3dB Beamwidth	20 degrees
Polarization	circular polarization
Size	length 31cm, dia 14cm
Axial Ratio	< 1.5dbi

This circularly polarized helical antenna designed for reliable wireless communication across 5.72–5.88 GHz frequency band. Its circular polarization minimizes signal degradation caused by multipath reflections and antenna misalignment, making it ideal for drone jamming, telemetry systems, video transmission links, tracking applications, and other long-range wireless networks requiring high-performance connectivity.


VSWR

Voltage Standing Wave Ratio (VSWR)




S11

S-Parameters [Magnitude]




Gain

Max Gain over Frequency



Axial Ratio

Axial Ratio




AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.




Radiation Patterns: Red = Phi 0; Green = Phi 90


5.72GHz




5.75GHz




5.78GHz




5.81GHz



5.84GHz



5.88GHz



AntennaTec may update or improve these specifications from time to time to enhance product design, manufacturing, or performance. This document contains official AntennaTec product information and must not be reproduced, modified, or used for commercial purposes without written permission from AntennaTec.

